

MINISTRY OF SUPPLY (DIED(A)/R.A.E.)VALVE ELECTRONIC

Specification MAP/CV 1874 Issue 2 Dated 14.2.52 To be read in conjunction with K1001	<u>SECURITY</u>	
	<u>Specification</u>	<u>Valve</u>
	UNCLASSIFIED	UNCLASSIFIED

→ Indicates a change

TYPE OF VALVE: Dummy Load Lamp ENVELOPE: Glass		<u>MARKING</u> See K1001/4		
<u>RATING</u>		<u>BASE</u> B4		
Resistance (ohms)	600	<u>CONNECTIONS</u>		
Max. Power (W)	100			
Note		Pin	Electrode	
		1	No connection	
		2	No connection	
		3	Filament	
		4	Filament	
		<u>DIMENSIONS (mm)</u>		
		See K1001/A1/D1		
		Dimension A (max.)	150	
		Dimension B (max.)	80	
<u>NOTE</u>				
A. The lamp shall be suitable for use up to 20 Mc/s				
<u>TEST</u>				
To be performed in addition to those applicable in K1001				
Test Conditions	Test	Limits		No. Tested
		Min.	Max.	
Lamp to be run for 2 minutes (min), with an applied voltage of 245V. min, 270V. max., AC, RMS. Frequency = 50c/s	Resistance (ohms)	540	660	100%

CV1874/2/1