

Specification MOS/CV4056	<u>SECURITY</u>	
Issue 2 Dated 23 Nov 1956	<u>Specification</u>	<u>Valve</u>
→ To be read in conjunction with K1001, BS448 and BS1409	UNCLASSIFIED	UNCLASSIFIED

TYPE OF VALVE	- Reliable Video Output - Pentode, with flexible leads	<u>MARKING</u> K1001/4		
CATHODE	- Indirectly-heated	<u>BASE</u> B9i/F		
ENVELOPE	- Glass	<u>DIMENSIONS</u> See K1001/AI/D11		
PROTOTYPE	- CV2127; 6CH6			
EQUIVALENT PINNED VALVE	- CV4055			
<u>RATING, CONNECTIONS, CAPACITANCES and NOTES</u> See Specification MOS/CV4055, issue 2 dated 23 Nov 1956		<u>Dimensions (mm)</u>	<u>Min</u>	<u>Max</u>
		A. Seated height	-	60.3
		B. Diameter	19.0	22.2
		D. Lead length	38	-
		<u>MOUNTING POSITION</u> Any		

TESTS

The tests required by Specification MOS/CV4055, issue 2 dated 23 Nov 1956 shall be performed except as follows:-

K1001	Test	Test Conditions	AQL %	Insp. Level	Sym-bol	Limits	Units
	<u>GROUP D</u> DELETE -						
→ 7.2	Base Strain	No voltages	6.5	IA			
	ADD -						
5.12	Lead Fragility	No voltages	6.5	IA			