

Medium-Mu Twin Triode

9-PIN MINIATURE TYPE

For Applications Critical as to Microphonics

GENERAL DATA

Electrical:

Heater, for Unipotential Cathodes:

Heater arrangement	<i>Series</i>	<i>Parallel</i>	
Voltage (AC or DC)	12.6	6.3 ± 10%	volts
Current	0.15 ± 6%	0.3	amp

Direct Interelectrode Capacitances (Approx.):*

	<i>Unit No.1</i>	<i>Unit No.2</i>	
Grid to plate	1.5	1.5	μμf
Grid to cathode and heater. . .	1.6	1.6	μμf
Plate to cathode and heater . .	0.5	0.35	μμf

Characteristics, Class A₁ Amplifier (Each Unit):

Plate Voltage	100	250	volts
Grid Voltage.	0	-8.5	volts
Amplification Factor.	19.5	17	
Plate Resistance (Approx.). . . .	6250	7700	ohms
Transconductance.	3100	2200	μmhos
Plate Current	11.8	10.5	ma
Grid Voltage (Approx.) for plate μa = 10	-	-24	volts

Mechanical:

Operating Position.	Any
Maximum Overall Length.	2-3/16"
Maximum Seated Length	1-15/16"
Length, Base Seat to Bulb Top (Excluding tip). . .	1-9/16" ± 3/32"
Diameter.	0.750" to 0.875"
Dimensional Outline	See <i>General Section</i>
Bulb.	T6-1/2
Base.	Small-Button Noval 9-Pin (JEDEC No.E9-1)
Basing Designation for BOTTOM VIEW.	9A

Pin 1- Plate of Unit No.2		Pin 6- Plate of Unit No.1
Pin 2- Grid of Unit No.2		Pin 7- Grid of Unit No.1
Pin 3- Cathode of Unit No.2		Pin 8- Cathode of Unit No.1
Pins 4 & 9- Heater of Unit No.2		Pin 9- Heater Tap
Pins 5 & 9- Heater of Unit No.1		

← Indicates a change.



12AU7A

AMPLIFIER — Class A₁

Values are for Each Unit

→ Maximum Ratings, Design-Maximum Values:

PLATE VOLTAGE	330	max.	volts
CATHODE CURRENT	22	max.	ma
PLATE DISSIPATION:			
Either plate.	2.75	max.	watts
Both plates (Both units operating).	5.5	max.	watts
PEAK HEATER-CATHODE VOLTAGE:			
Heater negative with respect to cathode.	200	max.	volts
Heater positive with respect to cathode.	200 ^b	max.	volts

Typical Operation as Resistance-Coupled Amplifier:

See *RESISTANCE-COUPLED AMPLIFIER CHART No. 10*
at front of this Section

Maximum Circuit Values:

Grid-Circuit Resistance:			
For fixed-bias operation.	1	max.	megohm

HORIZONTAL-DEFLECTION OSCILLATOR

Values are for Each Unit

→ Maximum Ratings, Design-Maximum Values:

For operation in a 525-line, 30-frame system^c

DC PLATE VOLTAGE.	330	max.	volts
PEAK NEGATIVE-PULSE GRID VOLTAGE.	660	max.	volts
CATHODE CURRENT:			
Peak.	330	max.	ma
Average	22	max.	ma
PLATE DISSIPATION:			
Either plate.	2.75	max.	watts
Both plates (Both units operating).	5.5	max.	watts
PEAK HEATER-CATHODE VOLTAGE:			
Heater negative with respect to cathode.	200	max.	volts
Heater positive with respect to cathode.	200 ^b	max.	volts

Maximum Circuit Values:

Grid-Circuit Resistance	2.2	max.	megohms
-----------------------------------	-----	------	---------

VERTICAL-DEFLECTION OSCILLATOR

Values are for Each Unit

→ Maximum Ratings, Design-Maximum Values:

For operation in a 525-line, 30-frame system^c

DC PLATE VOLTAGE.	330	max.	volts
PEAK NEGATIVE-PULSE GRID VOLTAGE.	440	max.	volts
CATHODE CURRENT:			
Peak.	66	max.	ma
Average	22	max.	ma

→ Indicates a change.



PLATE DISSIPATION:

Either plate.	2.75	max.	watts
Both plates (Both units operating). . .	5.5	max.	watts

PEAK HEATER-CATHODE VOLTAGE:

Heater negative with respect to cathode.	200	max.	volts
Heater positive with respect to cathode.	200 ^b	max.	volts

Maximum Circuit Values:

Grid-Circuit Resistance	2.2	max.	megohms
-----------------------------------	-----	------	---------

VERTICAL-DEFLECTION AMPLIFIER

Values are for Each Unit

Maximum Ratings, Design-Maximum Values:

For operation in a 525-line, 30-frame system^c

DC PLATE VOLTAGE.	300	max.	volts
PEAK POSITIVE-PULSE PLATE VOLTAGE ^d	1200	max.	volts
PEAK NEGATIVE-PULSE GRID VOLTAGE.	275	max.	volts

CATHODE CURRENT:

Peak.	66	max.	ma
Average	22	max.	ma

PLATE DISSIPATION:

Either plate.	2.75	max.	watts
Both plates (Both units operating). . .	5.5	max.	watts

PEAK HEATER-CATHODE VOLTAGE:

Heater negative with respect to cathode.	200	max.	volts
Heater positive with respect to cathode.	200 ^b	max.	volts

Maximum Circuit Values:

Grid-Circuit Resistance:			
For cathode-bias operation.	2.2	max.	megohms

^a Without external shield.

^b The dc component must not exceed 100 volts.

^c As described in "Standards of Good Engineering Practice Concerning Television Broadcast Stations," Federal Communications Commission.


^d This rating is applicable where the duration of the voltage pulse does not exceed 15 per cent of one vertical scanning cycle. In a 525-line, 30-frame system, 15 per cent of one vertical scanning cycle is 2.5 milliseconds.

← Indicates a change.



12AU7A

AVERAGE PLATE CHARACTERISTICS Each Unit




92CM-10548



AVERAGE CHARACTERISTICS Each Unit

$E_f = 12.6$ VOLTS
SERIES HEATER ARRANGEMENT.



92CM-8564R2





12AU7-A

MEDIUM-MU TWIN TRIODE

9-PIN MINIATURE TYPE

For applications critical as to microphonics

The 12AU7-A has the same *maximum ratings, characteristics, typical operation, mechanical data, and curves* as the 12AU7.