



6074

## VOLTAGE REGULATOR

MINIATURE GLOW-DISCHARGE TYPE

Intended for applications where very stable characteristics and dependable performance under shock and vibration are paramount. The 6074 is a "premium" version of the OB2.

~~6074~~  
PREMIUM TYPE

## DATA


## General:

Cathode. . . . . Cold

## Mechanical:

Mounting Position. . . . .	Any
Maximum Overall Length. . . . .	2-5/8"
Maximum Seated Length. . . . .	2-3/8"
Length, Base Seat to Bulb Top (Excluding tip). . . . .	2" ± 3/32"
Maximum Diameter. . . . .	3/4"
Bulb. . . . .	T-5-1/2
Base. . . . .	Small-Button Miniature 7-Pin (JETEC No. E7-1)
Basing Designation for BOTTOM VIEW . . . . .	5BQ

Pin 1 - Anode  
 Pin 2 - Cathode  
 Pin 3 - Internal  
 Connection-  
 Do Not Use  
 Pin 4 - Cathode



Pin 5 - Anode  
 Pin 6 - Internal  
 Connection-  
 Do Not Use  
 Pin 7 - Cathode

## Maximum Ratings, Absolute Values:

AVERAGE STARTING CURRENT (See note below)	75 max.	ma
DC CATHODE CURRENT . . . . .	{ 30 max. 5 min.	ma
AMBIENT TEMPERATURE RANGE. . . . .	-55 to +90	°C
FREQUENCY. . . . .	0 max.	cps

## Characteristics Range Values for Equipment Design:

	Min.	Av.	Max.	
DC Anode-Supply Voltage. . . . .	133▲	-	-	volts
Anode Breakdown Voltage. . . . .	-	115	133●	volts
Anode Voltage Drop . . . . .	101★	108	114●	volts
Regulation (5 to 30 ma). . . . .	-	1	4★	volts

## Circuit Values:

Shunt Capacitor. . . . . - - - 0.1  $\mu$ f  
 Series Resistor. . . . . . . . . . . . . See note below

NOTE: The notes and circuit information shown under Type OA2 are also applicable to the 6074.

▲, ●, ★: See next page.

MAY 1, 1952

TUBE DEPARTMENT  
 RADIO CORPORATION OF AMERICA, HARRISON, NEW JERSEY

TENTATIVE DATA

6074



6074

## VOLTAGE REGULATOR

### Shock and Vibration Tests:

These tests are made as indicated in the JAN Specifications JAN 1-A for Electron Tubes, May, 1946 under the sections as follows:

#### Section F-6b (9e) Shock Test:

Instantaneous Impact Acceleration . . . . . 900 max. 9

#### Section F-6b (9f) Vibration Test:

Vibrational Acceleration . . . . . 2.5 max. 9

- ▲ Not less than indicated supply voltage should be provided to insure "starting" throughout tube life.
- Maximum individual tube value during life.
- ★ Minimum individual tube value during life.

MAY 1, 1952

TENTATIVE DATA

TUBE DEPARTMENT

RADIO CORPORATION OF AMERICA, HARRISON, NEW JERSEY