

# Twin Diode— Sharp-Cutoff Pentode

9-PIN MINIATURE TYPE

With Heater Having Controlled Warm-Up Time

## GENERAL DATA

### Electrical:

Heater, for Unipotential Cathodes:

Voltage (AC or DC) . . . . .	8	volts
Current . . . . .	0.6 ± 6%	amp
Warm-up time (Average) . . . . .	11	sec

Direct Interelectrode Capacitances:<sup>a</sup>

#### Diode Units:

Either plate to cathode & internal shield, pentode grid No.3 & pentode cathode & pentode internal shield, and heater . . . . .	1.5	μf
Cathode & internal shield to either plate, pentode grid No.3 & pentode cathode & pentode internal shield, and heater . . . . .	7.5	μf

#### Pentode Unit:

Grid No.1 to plate . . . . .	0.1 max.	μf
Grid No.1 to cathode & grid No.3 & internal shield, grid No.2, diode-units cathode & diode-units internal shield, and heater . . . . .	10	μf
Plate to cathode & grid No.3 & internal shield, grid No.2, diode-units cathode & diode-units internal shield, and heater . . . . .	4.2	μf
Pentode grid No.1 to either diode plate . . . . .	0.005 max.	μf
Pentode plate to either diode plate . . . . .	0.02 max.	μf

### Characteristics, Class A<sub>1</sub> Amplifier (Pentode Unit):

Plate Supply Voltage . . . . .	60	200	volts
Grid-No.2 Supply Voltage . . . . .	150	150	volts
Grid-No.1 Voltage . . . . .	0	-	volts
Cathode Resistor . . . . .	-	100	ohms
Plate Resistance (Approx.) . . . . .	-	60000	ohms
Transconductance . . . . .	-	11500	μmhos
Plate Current . . . . .	55 <sup>b</sup>	25	ma
Grid-No.2 Current . . . . .	18 <sup>b</sup>	5.5	ma
Grid-No.1 Voltage (Approx.) for plate μ <sub>a</sub> = 100 . . . . .	-	-10	volts

### Mechanical:


Operating Position . . . . .	Any
Maximum Overall Length . . . . .	2-5/8"
Maximum Seated Length . . . . .	2-3/8"
Length, Base Seat to Bulb Top (Excluding tip) . . . . .	2" ± 3/32"
Diameter . . . . .	0.750" to 0.875"



# 8ET7

Dimensional Outline. . . . . See *General Section*  
Bulb . . . . . T6-1/2  
Base . . . . . Small-Button Noval 9-Pin (JEDEC No.E9-1)  
Basing Designation for BOTTOM VIEW . . . . . 9LT

Pin 1 - Diode-Units  
Cathode,  
Internal  
Shield  
Pin 2 - Diode  
Plate No.2  
Pin 3 - Diode  
Plate No.1  
Pin 4 - Heater  
Pin 5 - Heater



Pin 6 - Pentode  
Grid No.3,  
Cathode,  
Internal  
Shield  
Pin 7 - Pentode  
Grid No.1  
Pin 8 - Pentode  
Grid No.2  
Pin 9 - Pentode Plate

## PENTODE — AMPLIFIER — Class A<sub>1</sub>

### Maximum Ratings, Design-Maximum Values:

PLATE VOLTAGE. . . . . 330 max. volts  
GRID-No.2 (SCREEN-GRID) SUPPLY VOLTAGE . . . 330 max. volts  
GRID-No.2 VOLTAGE. . . . . See *Grid-No.2 Input Rating*  
Chart at front of Receiving Tube Section

GRID-No.1 (CONTROL-GRID) VOLTAGE:  
Positive-bias value. . . . . 0 max. volts  
GRID-No.2 INPUT:  
For grid-No.2 voltages up to 165 volts . . . 1.1 max. watts  
For grid-No.2 voltages between 165  
and 330 volts. . . . . See *Grid-No.2 Input Rating*  
Chart at front of Receiving Tube Section

PLATE DISSIPATION. . . . . 5 max. watts  
PEAK HEATER-CATHODE VOLTAGE:  
Heater negative with respect to cathode. 200 max. volts  
Heater positive with respect to cathode. 200<sup>c</sup> max. volts

### Maximum Circuit Values:

Grid-No.1-Circuit Resistance:  
For fixed-bias operation . . . . . 0.1 max. megohm  
For cathode-bias operation . . . . . 0.25 max. megohm

## DIODE UNITS — Two

*Values are for Each Unit*

### Maximum Ratings, Design-Maximum Values:

DC PLATE CURRENT . . . . . 3 max. ma  
PEAK HEATER-CATHODE VOLTAGE:  
Heater negative with respect to cathode. 200 max. volts  
Heater positive with respect to cathode. 200<sup>c</sup> max. volts

### Characteristics, Instantaneous Test Condition:

Plate Current for plate volts = 10 . . . . . 1.5 ma

<sup>a</sup> Without external shield.

<sup>b</sup> This value can be measured by a method involving a recurrent wave form such that the maximum ratings of the tube will not be exceeded.

<sup>c</sup> The dc component must not exceed 100 volts.

