

TUNG-SOL

DOUBLE-DIODE PENTODE


COATED UNIPOTENTIAL CATHODE

HEATER


12.6 VOLTS 150 MA.

AC OR DC

ANY MOUNTING POSITION



GLASS BULB



BOTTOM VIEW

LOCK-IN
8 PIN BASE
8AE

THE 14E7 IS A COMBINED REMOTE CUT OFF PENTODE AND DOUBLE DIODE DETECTOR USING THE LOCK-IN CONSTRUCTION. IT IS DESIGNED FOR USE AS A COMBINED DETECTOR, AVC RECTIFIER AND RF, IF OR AF AMPLIFIER.

DIRECT INTERELECTRODE CAPACITANCES

WITH RMA SHIELD #308 CONNECTED TO CATHODE

GRID TO PLATE: (G_1 TO P) MAX.	0.005	μf
INPUT: G_1 TO ($H+K+G_2+IS$)	4.6	μf
OUTPUT: P TO ($H+K+G_2+IS$)	5.5	μf
DIODE #1 TO GRID (1P TO G_1) MAX.	0.013	μf
DIODE #2 TO GRID (2P TO G_1) MAX.	0.003	μf

RATINGS

INTERPRETED ACCORDING TO RMA STANDARD M8-210

HEATER VOLTAGE	12.6	VOLTS
MAXIMUM HEATER-CATHODE VOLTAGE	90	VOLTS
MAXIMUM PLATE VOLTAGE	300	VOLTS
MAXIMUM GRID #2 VOLTAGE	100	VOLTS
MAXIMUM GRID #2 SUPPLY VOLTAGE	300	VOLTS
MAXIMUM POSITIVE DC GRID #1 VOLTAGE	0	VOLTS
MAXIMUM PLATE DISSIPATION	2	WATTS
MAXIMUM SCREEN DISSIPATION	0.3	WATT
MAXIMUM VOLTAGE DROP MEASURED WITH TUBE CONDUCTING 0.8 MA. EACH PLATE	10	VOLTS
MAXIMUM DIODE CURRENT EACH PLATE FOR CONTINUOUS OPERATION	1	MA.

TYPICAL OPERATING CONDITIONS AND CHARACTERISTICS

RF OR IF AMPLIFIER

HEATER VOLTAGE	12.6	12.6	VOLTS
HEATER CURRENT	150	150	MA.
PLATE VOLTAGE	100	250	VOLTS
GRID #2 VOLTAGE	100	100	VOLTS
GRID #1 VOLTAGE	-1	-3	VOLTS
PLATE CURRENT	10	7.5	MA.
GRID #2 CURRENT	2.7	1.6	MA.
PLATE RESISTANCE (APPROX.)	0.15	0.7	MEGOHM
TRANSCONDUCTANCE	1 600	1 300	μ MHOS
GRID #1 VOLTAGE (APPROX.) FOR TRANSCONDUCTANCE = 2 μ MHOS	-36	-42.5	VOLTS

PLATE
2277
NOV. 1,
1949

14E7(7E7)

